
4THEWALL

DLP Rear Projection Display Cube

Laser Light Source
SLIM CUBES (FHD)





4THEWALL | DLP Rear Projection Display Cube Laser Light Source SLIM CUBES (FHD)

- Physical Gap $\leq 0.2\text{mm}$
- 24/7 Continuous Running
- Modular Design Lead to Ease of Maintenance
- Super High Brightness
- Wide Color Gamut Lead to Exquisite Image
- Long Lifetime
- RoHS & WEEE Compliance, IP6X Dustproof





4THE WALL | DLP Rear Projection Display Cube Laser Light Source SLIM CUBES (FHD)

MODEL		DLP Series	
		SC-DLP60 S	SC-DLP70 S
		60"	70"
Projection Engine	Working Resolution	640×480@60Hz~1920×1200@60Hz	
	Brightness	800 ANSI Lumens	
	Brightness Uniformity	≥90%	
	Noise Level	≤26db (Cube Body)	
	Dust Proof Level	IP6X	
	Signal Input	DVI/VGA (DVI-I), HDMI (HDMI A), CVBS (BNC), USB (USB A)	
	Control Input	RS232 (RJ-45); IR Remote (IR Receiver)	
	Control Output	RS232×2 (RJ-45)	
	Static Contrast Ratio	2500:1	
	Working Conditions	Power Consumption	200W
Power Supply		AC 100-240V,50/60Hz	
Operating Temperature		5-35° C	
Operating Humidity		20-90% (Non-condensing)	