

49N500B35

49" LCD Videowall



- Optional FRC up to 120Hz
- 10 Bit LVDS
- Support 3840 x 2160/30Hz
- 4K Signal Input
- Any input signal can be 4K looped & output by DP
- Temperature Control Function
- Sleep Mode
- Auto Adjust
- 3D MADI Combfilter

Narrow Bezel

Bezel to bezel 3.5 mm video wall displays with 49 inch 500 nits will create visually stunning digital wall that is easily installed, maintained and managed.

Wide Viewing Angle

ADS technology allows you to watch the screen virtually at any angle. It is ideal for small scale meeting rooms to large scale conference rooms.

Brightness Uniformity

It ensures high-quality, even image and light delivered across displays.

24/7 Reliable

4TheWall Video wall screens are design for use in 24/7 control rooms and the critical environments that demand continuous operation

Management

You can manage your Video wall panel over your PC with control management software.



Input and Output

Inputs	HDMIx2,VGAx1,DVIx1,DPx1,RS232, 1x3.5mm Audio Port
Outputs	DPx1 and RS232
Audio Outputs	1x3.5mm Audio Output
Resolutions	3840x2160@30Hz

Panel Specifications

LCD Technology	ADS
Aspect Ratio	16:9
Luminance	500Cd/m2
Contrast Ratio	Static: 1400:1 / Dynamic: 500.000:1
Color Depth	16,7 M (8Bit)
Viewing Angle	178°
Response Time	8ms
Life Time	50.000 Hours
Screen Bezel	2.3mm(U/L), 1.2mm(R/B)
Bezel to Bezel	3.5mm

General Features

Power Supply	AC100~240V (+/-10%), 50/60 Hz
Power Consumption(Standard)	120W
Power Consumption(Standby)	≤0.5W
Net Weight	24 kg
Gross Weight	30.5 kg
Dimensions	1078.4mm×608.4mm×120.8mm- W/H/D
Working Temperature	5°C~40°C
Humidity Range	20%~80%

Certifications

EU/US	CE
-------	----

