

## Wall28/1204CDBlack

Powerful, Designed to Work 24/7 Videowall Controller

Model Number:110723104850

## Neg ATHEWALL

## **Features**


- · Supports 7 module
- Each output module supports up to 4 output channel
- · Each input module supports up to 4 input channel
- 4 x 4K@60Hz HDMI Output
- 12 x 4K Mini HDMI Input
- Videowall HTTP Stream Feature
- Automatic Switching Meeting Mode
- · Remote Control (optional) Tablet/IR)
- Automation control unit Ethernet input and output, RS232 input and output
- HDCP 2.2 Support

## **Overview**

Easy to use video wall controller, has strong features with Designer V5 software and supports 4K inputs and outputs

Wall28 can be used for command control centers, monitoring centers, meeting rooms and designed to work 24/7

Automation control protocols such as KNX, Dali, RS232, DMX512 etc.Unlimited scenarios can be designed with CPanel automation design software





<b>Technical Specifications</b>	Wall28/12	204CDBlack #110723104850	
Hardware			
CPU	Intel i9 Quad core 3.5GHz CPU - optional 4.0GHz		
RAM	16 GB DDR4 - optional 32 GB DDR4		
Hard Disk	2 x 240GB - optional 500GB SSD		
Operating System	Windows 10 Pro / LTSC		
Network Connection			
Ethernet	2x IP 1Gbit and Wireless		
IP Address Feature	DHCP, IPV4, IPV6 and Static		
General Features			
Power Supply	100 - 240V, 50-60Hz, 10-5 Amp		
Working Temperature	0°C~50°C		
Working Humidity Range	20~80% RH (no condensation)		
Storage Temperature	-20°C~60°C		
ESD Protection	±8kV (air-gap discharge) ±4kV (contact discharge)		
Dimensions	482mm ×452 mm × 178mm - W/D/H		
Weight	23 kg		
Power Value	600 W		
Mounting	Rack Cabinet		
Certification			
EU/USA	CE and ROHS DoC		
Package Details			
Dimension (packaged)	482mm x 452mm x 178mm - W/D/H		
Weight (packaged)	25 kg		
Package Content	1 x Wall28 Chassis, Mini HDMI(E) to HDMI(E) Cable, Power Cable , User Manual		
		Wall28	
Input		12 x 4K@30 Hz - Mini HDMI (Type-C) Supported Resolutions 4096x2160 @ 60Hz, 4096x2160 @ 30Hz, 3840x2160 @ 60Hz, 3840x2160 @ 30Hz	
Output		4 x 4K@60Hz Output - 8 x DP or 8 x HDMI Supported Resolutions 5120x3200@60Hz (DP 1.4), 4096x2160@60Hz (HDMI)	
H.264 Decoding		12 x 1080p@30 stream	
Codec		H.264/MPEG-4 Part 10 (AVC), Up to Level 5.2	
H.264 Profile		Main Profile (BP), Main Profile (MP), High Profile (HiP),	

Yes



RTSP Multicast and Unicast